

# Viton A Insertion Rubber Sheet

Reglin Viton A Insertion is a premium grade 75 Duro oil, fuel, chemical and heat resistant rubber sheet with nomex reinforcement.

## FEATURES

Reglin Viton A Insertion Rubber Sheet is made from a premium fluoroelastomer compound and will display very high temperature and excellent resistance to a broad range of chemicals and aggressive acids.

Viton A Insertion rubber is reinforced with a nomex fabric which gives improved tear strength and dimensional stability.

Viton A exhibits excellent resistance to oil and petroleum-based products including a diverse range of fuels, greases, solvents and hydraulic fluids. It is also resistant to mineral acids, aliphatic and aromatic hydrocarbons.

Viton has excellent ozone/UV resistance making it weather resistant and suitable for prolonged outdoor use. It has good physical properties including mechanical strength and will maintain its fluid resistance and flexibility across a wide temperature range.



## TECHNICAL INFORMATION

Polymer	FKM	
Reinforcement	Nomex	
Fluorine Content	66% (min)	
Specific Gravity	1.85	ASTM D297
Hardness	75° ± 5° Shore A	ASTM D2240
Tensile Strength	7 MPa (min)	ASTM D412
Elongation @ Break	175% (min)	ASTM D412
Temperature Range	-10°C to +250°C	

## AVAILABLE SIZES

Reglin stock Viton A Insertion Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
VITONAINS01.5	1.5mm x 1200mm (10 L/M Rolls)	3.5 kgs
VITONAINS03	3mm x 1200mm (10 L/M Rolls)	7 kgs