

Viton A Rubber Sheet

Reglin Viton A is a premium grade 70 Duro oil, fuel, chemical and heat resistant rubber sheet.

FEATURES

Reglin Viton A Rubber Sheet is made from a premium fluoroelastomer compound and will display very high temperature and excellent resistance to a broad range of chemicals and aggressive acids.

Viton A exhibits excellent resistance to oil and petroleum-based products including a diverse range of fuels, greases, solvents and hydraulic fluids. It is also resistant to mineral acids, aliphatic and aromatic hydrocarbons.

Viton has excellent ozone/UV resistance making it weather resistant and suitable for prolonged outdoor use. It has good physical properties including mechanical strength and will maintain its fluid resistance and flexibility across a wide temperature range.



TECHNICAL INFORMATION

Polymer	FKM	
Fluorine Content	66% (min)	
Colour	Black	
Specific Gravity	1.85	ASTM D297
Hardness	70° ± 5° Shore A	ASTM D2240
Tensile Strength	7 MPa (min)	ISO 37
Elongation @ Break	200% (min)	ISO 37
Temperature Range	-10°C to +250°C	

AVAILABLE SIZES

Reglin stock Viton A Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
VITONA0.5	0.5mm x 1200mm (10 L/M Rolls)	1.2 kgs
VITONA01	1mm x 1200mm (10 L/M Rolls)	2.4 kgs
VITONA01.5	1.5mm x 1200mm (10 L/M Rolls)	3.5 kgs
VITONA02	2mm x 1200mm (10 L/M Rolls)	4.7 kgs
VITONA03	3mm x 1200mm (10 L/M Rolls)	17.2 kgs
VITONA031500	3mm x 1500mm (10 L/M Rolls)	8.6 kgs
VITONA05	5mm x 1200mm (10 L/M Rolls)	11.7 kgs
VITONA06	6mm x 1200mm (10 L/M Rolls)	14.1 kgs
VITONA08	8mm x 1200mm (5 L/M Rolls)	18.7 kgs
VITONA10	10mm x 1200mm (5 L/M Rolls)	23.4 kgs