Sheet Rubber



Viton B Rubber Sheet

Reglin Viton B is a premium grade 75 Duro oil, fuel, chemical and heat resistant rubber sheet.

FEATURES

Reglin Viton B Rubber Sheet is made from a premium fluoroelastomer compound and will display very high temperature and excellent chemical resistance. It will display superior fluid resistance to both diluted and concentrated aggressive acids and will retain flexibility better after dry heat ageing compared to Viton A.

Viton B exhibits excellent resistance to oil and petroleumbased products including a diverse range of fuels, greases, solvents and hydraulic fluids. It is also resistant to mineral acids, aliphatic and aromatic hydrocarbons.

Viton B has excellent ozone/UV resistance making it weather resistant and suitable for prolonged outdoor use. It has good physical properties including mechanical strength and will maintain its fluid resistance and flexibility across a wide temperature range.



TECHNICAL INFORMATION

Polymer	FKM	
Fluorine Content	68% (min)	
Colour	Black	
Specific Gravity	1.81	ASTM D297
Hardness	75° ± 5° Shore A	ASTM D2240
Tensile Strength	8.5 MPa (min)	ASTM D412
Elongation @ Break	175% (min)	ASTM D412
Compression Set 22 hrs @ 200°C	30%	ASTM D395B
Fluid Resistance 70 hrs @ 20°C in toluene	20% maximum swell	ASTM D471
Temperature Range	-18°C to +220°C	

AVAILABLE SIZES

Reglin stock Viton B Rubber Sheet in a standard thickness and roll size. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
VITONB03	3mm x 1200mm (10 L/M Rolls)	6.6 kgs



www.reglinrubber.com.au