

Commercial Natural Insertion Rubber Sheet

Reglin Commercial Natural Insertion is an economical grade general purpose rubber sheet with cotton reinforcement.

FEATURES

Reglin Commercial Natural Insertion Rubber Sheet is made from a blended Natural rubber compound.

Commercial Natural Insertion has moderate physical properties including mechanical strength and abrasion resistance.



TECHNICAL INFORMATION

Polymer	NR/SBR	
Colour	Black	
Reinforcement	Cotton	
Specific Gravity	1.55	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	3.5 MPa (min)	ASTM D412
Elongation @ Break	250% (min)	ASTM D412
Temperature Range	0°C to +65°C	

AVAILABLE SIZES

Reglin stock Commercial Natural Insertion Rubber Sheet in a range of standard thicknesses and roll sizes.

PART NO.	SIZE	WEIGHT (PER L/M)
CNRI01X1	1.5mm x 1200mm x 1 Ply (10 L/M Rolls)	2.7 kgs
CNRI01X11500	1.5mm x 1500mm x 1 Ply (10 L/M Rolls)	3.4 kgs
CNRI03X1	3mm x 1200mm x 1 Ply (10 L/M Rolls)	5.4 kgs
CNRI03X11500	3mm x 1500mm x 1 Ply (10 L/M Rolls)	7 kgs
CNRI03X2	3mm x 1200mm x 2 Ply (10 L/M Rolls)	6.1 kgs
CNRI04X2	4mm x 1200mm x 2 Ply (10 L/M Rolls)	8.1 kgs
CNRI04X21500	4mm x 1500mm x 2 Ply (10 L/M Rolls)	10.1 kgs
CNRI06X2	6mm x 1200mm x 2 Ply (10 L/M Rolls)	10.8 kgs
CNRI06X21500	6mm x 1500mm x 2 Ply (10 L/M Rolls)	13.5 kgs
CNRI09X2	9mm x 1200mm x 2 Ply (10 L/M Rolls)	17.1 kgs
CNRI12X2	12mm x 1200mm x 2 Ply (10 L/M Rolls)	21.6 kgs