

# Conveyor Belt Sidewall

**Reglin Conveyor Belt Sidewall is a premium grade corrugated rubber edging designed to increase capacity of conveyor belts.**

## FEATURES

Reglin Conveyor Belt Sidewall is made from a highly elastic premium rubber compound and will display excellent resistance to abrasion and impact.

Reglin Sidewall is designed to be easily bonded to conveyor belt covers and to maintain flexibility in service. It has good ozone/UV resistance making it suitable for outdoor use.

Reglin Sidewall features a specifically designed corrugated profile to allow expansion and contraction of the edging. This ensures it will flex with the conveyor belt as it bends or wraps around pulleys.



## TECHNICAL INFORMATION

Polymer	NR	
Colour	Black	
Specific Gravity	1.12	ASTM D297
Hardness	60° ± 5° Shore A	ASTM D2240
Tensile Strength	15 MPa (min)	ASTM D412
Elongation @ Break	400% (min)	ASTM D412
Abrasion	140mm <sup>3</sup> (max) @ 10N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	80 N/mm (min)	ASTM D624

## AVAILABLE SIZES

Reglin Stock Conveyor Belt Sidewall in a range of standard sizes. It can also be supplied in cut lengths to suit your conveyor belt.

PART NO.	SIZE	WEIGHT (PER L/M)
CSW060	50mm x 60mm (100 L/M Rolls)	1.8 kgs
CSW080	50mm x 80mm (100 L/M Rolls)	2 kgs
CSW100	50mm x 100mm (100 L/M Rolls)	2.2 kgs
CSW120	50mm x 120mm (100 L/M Rolls)	2.4 kgs