

Filter Belt Sidewall Curbing

Reglin Filter Belt Curbing is a premium grade corrugated rubber edging designed to seal the edges of filter belts.

FEATURES

Reglin Filter Belt Curbing is made from a highly elastic premium rubber compound and will display excellent resistance to abrasion and impact.

Reglin Filter Belt Curbing is designed to be easily bonded to filter belt covers and to maintain flexibility in service. It has good ozone/UV resistance making it suitable for outdoor use.

Reglin Filter Belt Curbing features a specifically designed corrugated profile to allow expansion and contraction of the edging. This ensures it will flex with the filter belt as wraps around pulleys and can lay flat against the belt on the return side of the conveyor system.



TECHNICAL INFORMATION

Polymer	NR	
Colour	Black	
Specific Gravity	1.12	ASTM D297
Hardness	45° ± 5° Shore A	ASTM D2240
Tensile Strength	15 MPa (min)	ASTM D412
Elongation @ Break	600% (min)	ASTM D412
Abrasion	155mm ³ (max) @ 10N	ASTM D5963
Temperature Range	-20°C to +70°C	

AVAILABLE SIZES

Reglin stock Filter Belt Curbing in a standard profile. It can be supplied in cut lengths to suit your filter belt.

PART NO.	SIZE	WEIGHT (PER L/M)
FBE126	89mm x 126mm (100 L/M Rolls)	2.5 kgs