

Hypalon Rubber Sheet

Reglin Hypalon is a premium grade 65 Duro weather, corrosion and heat resistant rubber sheet.

FEATURES

Reglin Hypalon Rubber Sheet is made from a premium CSM rubber compound and will display high temperature and excellent chemical resistance to both acids and alkalis.

Hypalon has excellent ozone/UV resistance making it weather resistant and suitable for prolonged outdoor use. It has excellent physical properties including mechanical strength and will display good resistance to abrasion.

Hypalon displays superior insulating properties and high impermeability to fluids and moisture. It has good flame resistance and a high dielectric strength.



TECHNICAL INFORMATION

Polymer	CSM	
Polymer Content	100%	
Colour	Black	
Specific Gravity	1.35	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	9 MPa (min)	ASTM D412
Elongation @ Break	300% (min)	ASTM D412
Temperature Range	-25°C to + 120°C	
Tear Strength	20 N/mm (min)	ASTM D624

AVAILABLE SIZES

Reglin stock Hypalon Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
HYPR01.5	1.5mm x 1200mm (10 L/M Rolls)	2.5 kgs
HYPR03	3mm x 1200mm (10 L/M Rolls)	5 kgs
HYPR06	6mm x 1200mm (10 L/M Rolls)	10 kgs