

# Natural 40 HG Rubber Sheet

Natural 40 HG is a premium grade highly flexible and compressible resilient 40 Duro natural rubber sheet.

## FEATURES

Reglin Natural 40 HG Rubber Sheet is made from a highly elastic premium rubber compound and will display excellent resistance to abrasion.

Natural 40 HG has excellent physical properties including mechanical strength and tear resistance. It has ozone/UV resistance making it weather resistant and suitable for outdoor use.

Natural 40 HG is highly flexible and compressible. It has the capability for moderate load bearing.



## TECHNICAL INFORMATION

Polymer	NR	
Colour	Black	
Specific Gravity	1.12	ASTM D297
Hardness	40° ± 5° Shore A	ASTM D2240
Tensile Strength	18 MPa (min)	ASTM D412
Elongation @ Break	550% (min)	ASTM D412
Abrasion	100mm <sup>3</sup> (max) @5N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	60 N/mm (min)	ASTM D624

## AVAILABLE SIZES

Reglin stock Natural 40 HG Rubber sheet in a range of standard thicknesses including: 3mm, 6mm, 9mm, 12mm, 16mm 19mm and 25mm. It is available in a variety of roll sizes and can be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes to suit your application requirements.