

# Natural 60 Skirting Rubber

Reglin Natural 60 Skirting Rubber is a 60 Duro rubber designed for use as a conveyor sealing skirt.

## FEATURES

Natural 60 Skirting Rubber is made from a blended natural and synthetic rubber compound.

Natural 60 Skirting Rubber has physical properties which are designed to be worn by the conveyor belt to create a seal once installed and adjusted. This reduces material spillage but also minimizes the potential of damage to the conveyor belt itself.

Natural 60 Skirting Rubber can be supplied in full rolls or pre-cut skirting rubber strips to suit standard conveyor system designs, ready for easy installation.



## TECHNICAL INFORMATION

Polymer	NR/SBR	
Colour	Black	
Specific Gravity	1.55	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	3.5 MPa (min)	ASTM D412
Elongation @ Break	250% (min)	ASTM D412
Temperature Range	-20°C to +70°C	

### AVAILABLE SIZES

Reglin stock Natural 60 Skirting Rubber in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
NS150006	6mm x 1500mm (30 L/M Rolls)	14 kgs
NS150009	9mm x 1500mm (30 L/M Rolls)	21 kgs
NS150012	12mm x 1500mm (30 L/M Rolls)	27.9 kgs
NS150016	16mm x 1500mm (30 L/M Rolls)	37.2 kgs
NS150019	19mm x 1500mm (30 L/M Rolls)	44.2 kgs
NS150025	20mm x 1500mm (30 L/M Rolls)	58.2 kgs

### AVAILABLE STRIPS

Natural 60 Skirting Rubber is also stocked in a variety of pre-cut strips 6mm to 25mm thick in widths 75mm, 100mm, 125mm, 150mm, 200mm, 250mm and 300mm. It can also be supplied in custom widths or with a 45 degree bevel.