

Natural 65 Rubber Sheet

Reglin Natural 65 is a superior grade 65 Duro natural rubber sheet.

FEATURES

Natural 65 Rubber Sheet is made from a premium rubber compound and will display moderate resistance to abrasion.

Natural 65 has good physical properties including cut and tear resistance. It has ozone/UV resistance making it weather resistant and suitable for outdoor use.

It will also display resistance to some mild chemicals, including acids and alkalis.



TECHNICAL INFORMATION

Polymer	NR/SBR	
Colour	Black	
Specific Gravity	1.35	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	7 MPa (min)	ASTM D412
Elongation @ Break	350% (min)	ASTM D412
Abrasion	300 mm ³ (max) @ 10N	ASTM D5963
Temperature Range	-20°C to + 70°C	

AVAILABLE SIZES

Reglin stock Natural 65 Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
NRBR008	0.8mm x 1200mm (10 L/M Rolls)	1.3 kgs
NRBR01.5	1.5mm x 1200mm (10 L/M Rolls)	2.4 kgs
NRBR02.4	2.4mm x 1200mm (10 L/M Rolls)	3.9 kgs
NRBR03	3mm x 1200mm (10 L/M Rolls)	4.9 kgs
NRBR04.5	4.5mm x 1200mm (10 L/M Rolls)	7.3 kgs
NRBR06	6mm x 1200mm (10 L/M Rolls)	9.7 kgs
NRBR09	9mm x 1200mm (10 L/M Rolls)	15.4 kgs
NRBR12	12mm x 1200mm (10 L/M Rolls)	19.5 kgs