

Natural Heavy Duty Nylon Insertion Rubber Sheet

Reglin Natural Heavy Duty Nylon Insertion is a premium grade 65 Duro natural rubber sheet with high strength nylon reinforcement.

FEATURES

Reglin Natural Heavy Duty Nylon Insertion Rubber Sheet is made from a premium rubber compound and will display moderate resistance to abrasion and impact.

Natural Heavy Duty Nylon Insertion is reinforced with a high strength polyester nylon fabric which gives excellent cut and tear strength.

Natural Insertion has good physical properties and is extremely tough. It has ozone/UV resistance making it weather resistant and suitable for outdoor use.



TECHNICAL INFORMATION

Polymer	NR/SBR	
Colour	Black	
Reinforcement	Heavy Duty Nylon	
Specific Gravity	1.35	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Tensile Strength	7 MPa (min)	ASTM D412
Elongation @ Break	350% (min)	ASTM D412
Abrasion	300 mm ³ (max) @ 10N	ASTM D5963
Temperature Range	-25°C to +70°C	

AVAILABLE SIZES

Reglin stock Natural Heavy Duty Nylon Insertion Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
NNRI3X1	3mm x 1200mm x 1 Ply HD Nylon Reinforced (10 L/M Rolls)	4.4 kgs
NNRI6X1	6mm x 1200mm x 1 Ply HD Nylon Reinforced (10 L/M Rolls)	8.7 kgs
NNRI8X1	8mm x 1200mm x 1 Ply HD Nylon Reinforced (10 L/M Rolls)	11.5 kgs