

Fluorodyn Viton Caulk

Reglin Fluorodyn Viton Caulk is a highly flexible corrosion resistant fluoroelastomer sealant.

FEATURES

Reglin Fluorodyn Viton Caulk is made from a premium Viton compound and features 75% solids making it an easy to apply, single component sealant. It will display very high temperature and excellent resistance to a broad range of chemicals and aggressive acids.

Fluorodyn Viton caulk exhibits excellent resistance to oil and petroleum-based products including a diverse range of fuels, greases, solvents and hydraulic fluids. It is also resistant to mineral acids, aliphatic and aromatic hydrocarbons.

Viton Caulk has excellent ozone/UV resistance making it weather resistant and suitable for prolonged outdoor use. It has good physical properties including mechanical strength and will maintain its fluid resistance and flexibility across a wide temperature range.



TECHNICAL INFORMATION

Polymer Base	FKM
Colour	Black
Temperature Range	-28°C to +232°C

AVAILABLE SIZES

Reglin stock Fluorodyn Viton caulk in a standard size. It can also be supplied in other sizes upon request. Lead times and minimum order quantities apply to these products.

PART NO.	DESCRIPTION	WEIGHT (EACH)
GLFVC320	Fluorodyn Viton Caulk Sealant 320ml Cartridge	0.45 kgs