

MOW1 Rubberised Cork Sheet

Reglin MOW1 Cork is a superior grade 65 Duro rubberised cork sheet.

FEATURES

Reglin MOW1 Cork Sheet is made from a medium grain durable cork crumb bound together with a blended premium Nitrile rubber compound.

MOW1 Cork will display moderate resistance to oil and petroleum-based products including a range of fuels, solvents and lubrication fluids.

MOW1 Cork has good physical properties including compressive strength.



TECHNICAL INFORMATION

Binder Polymer	NBR	
Colour	Natural	
Density	0.7-0.8 g/cm ³	ASTM D297
Hardness	65± 5° Shore A	ASTM D2240
Cork Grain Size	Medium (1.55-2.0mm)	ASTM D412
Tensile Strength	0.9-1.5 MPa	ASTM D412
Temperature Range	-10° to +80°	
Compressibility	35-45% @ 28kg/cm ² load	
Recovery After Compression	85% (min)	
Oil Resistance 70hrs @ 100°C	Volume Swell OIL #3 +40%	ASTM D412

AVAILABLE SIZES

Reglin stock MOW1 Rubberised Cork Sheet in a range of standard thicknesses and sheet sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (EACH)
CKMOW01	1.6mm x 1040mm x 1040mm	1.4 kgs
CKMOW02.4	2.4mm x 1040mm x 1040mm	2 kgs
CKMOW03	3.2mm x 1040mm x 1040mm	2.6 kgs
CKMOW06	6.4mm x 1040mm x 1040mm	5 kgs
CKMOW09	9.5mm x 1040mm x 1040mm	6.7 kgs