

Capping Rubber

Reglin Capping Rubber is premium grade wear resistant rubber profile designed to cover steel stringer bars to protect screen cloths from wear and damage.

FEATURES

Reglin Capping Rubber is made from a premium EPDM rubber compound and will display good resistance to abrasion and impact.

Capping Rubber has excellent physical properties and will display good UV resistance making it weather resistant and suitable for outdoor use.

Capping Rubber is available in a range of different profiles to suit standard stringer bar sizes.



TECHNICAL INFORMATION

Polymer	EPDM	
Colour	Black	
Specific Gravity	1.20	ASTM D297
Hardness	75° ± 5° Shore A	ASTM D2240
Tensile Strength	10 MPa (min)	ASTM D412
Elongation @ Break	400% (min)	ASTM D412
Temperature Range	30°C to + 100°C	

AVAILABLE SIZES

Reglin stock Capping Rubber in a range of standard profiles. We can also supply custom profiles upon request. Minimum order quantities and lead times apply to custom made capping rubber.

PART NO.	DESCRIPTION	WEIGHT (PER L/M)
CR01	Capping Rubber R01 Square Top Long Leg 55mm Long to Suit 12mm Bar (20 L/M Rolls)	1.5 kgs
CR02	Capping Rubber R02 Round Top Long Leg 50mm Long to Suit 10mm Bar (20 L/M Rolls)	1.2 kgs
CR05	Capping Rubber R05 Round Top Short Leg 25mm Long to Suit 12mm Bar (20 L/M Rolls)	0.7 kgs
CR06	Capping Rubber R06 Round Top Short Leg 25mm Long to Suit 10mm Bar (20 L/M Rolls)	0.5 kgs
CR07	Capping Rubber R07 Square Top Long Leg 55mm Long to Suit 16mm Bar (20 L/M Rolls)	1.8 kgs