

Chutex 40 Rubber Sheet

Chutex 40 is a premium grade wear and tear resistant 40 Duro natural rubber sheet.

FEATURES

Chutex 40 Rubber sheet is made from a highly elastic premium natural rubber compound and will display excellent resistance to wet slurry and fine particle sliding abrasion.

Chutex 40 has excellent physical properties including cut and tear resistance and is extremely flexible. It will also display resistance to some mild chemicals, including acids and alkalis used in mineral processing.



TECHNICAL INFORMATION

Polymer	NR	
Colour	Pink	
Specific Gravity	1.05	ASTM D297
Hardness	40° ± 5° Shore A	ASTM D2240
Tensile Strength	18 MPa (min)	ASTM D412
Elongation @ Break	550% (min)	ASTM D412
Abrasion	95mm ³ (max) @ 5N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	60 N/mm (min)	ASTM D624

AVAILABLE SIZES

Reglin stock Chutex 40 Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	SIZE	WEIGHT (PER L/M)
CHX01.5	1.5mm x 1200mm (10 L/M Rolls)	1.9 kgs
CHX03	3mm x 1200mm (10 L/M Rolls)	3.9 kgs
CHX04.5	4.5mm x 1200mm (10 L/M Rolls)	5.8 kgs
CHX06	6mm x 1200mm (10 L/M Rolls)	7.7 kgs
CHX091200	9mm x 1200mm (10 L/M Rolls)	11.5 kgs
CHX091500	9mm x 1500mm (10 L/M Rolls)	14.4 kgs
CHX121200	12mm x 1200mm (10 L/M Rolls)	12.8 kgs
CHX121500	12mm x 1500mm (10 L/M Rolls)	16 kgs
CHX161200	16mm x 1200mm (10 L/M Rolls)	17.1 kgs
CHX161500	16mm x 1500mm (10 L/M Rolls)	21.3 kgs
CHX191200	19mm x 1200mm (10 L/M Rolls)	20.3 kgs
CHX191500	19mm x 1500mm (10 L/M Rolls)	25.3 kgs
CHX251200	25mm x 1200mm (10 L/M Rolls)	26.8 kgs
CHX251500	25mm x 1500mm (10 L/M Rolls)	33.4 kgs