

# Reg-Lag 60 Sheet Lagging

Reg-Lag 60 Sheet Lagging is a premium grade wear resistant 60 Duro rubber pulley lagging sheet with CN bonding layer.

## FEATURES

Reg-Lag 60 Sheet Lagging is made from a highly elastic premium natural rubber compound and will display excellent resistance to abrasion. It will improve the coefficient of friction between the pulley and belt, reducing slippage.

Reg-Lag 60 Sheet Lagging features a diamond profile surface. This design prevents material buildup and assists with shedding dirt and water away from the pulley.

Reg-Lag 60 is supplied in roll form for easy application to the pulley in a single sheet.

Reg-Lag 60 features a specially formulated Neoprene based CN bonding layer to achieve ultimate adhesion when bonded to steel or rubber surfaces. The CN bonding layer is compatible with a wide range of Neoprene based rubber adhesives and allows for good bond strength to be achieved even in adverse conditions encountered on site.



## TECHNICAL INFORMATION

Polymer	NR/BR	
Colour	Black with CN bonding layer	
Specific Gravity	1.10	
Hardness	60° ± 5° Shore A	ASTM D2240
Tensile Strength	20 MPa (min)	ASTM D412
Elongation @ Break	450% (min)	ASTM D412
Abrasion	90 mm <sup>3</sup> (max) @ 10N	ASTM D5963
Temperature Range	-20°C to +70°C	
Tear Strength	80 N/mm (min)	ASTM D624

### AVAILABLE SIZES

Reglin stock Reg-Lag 60 Sheet Lagging in a range of standard thicknesses and roll sizes.

PART NO.	SIZE	WEIGHT (PER L/M)
DL081500	8mm x 1500mm with CN B/L (10 L/M Rolls)	18.6 kgs
DL081500M	8mm x 1500mm with CN B/L (10 L/M Rolls)	18.6 kgs
DL101500	10mm x 1500mm with CN B/L (10 L/M Rolls)	23.1 kgs
DL121500	12mm x 1500mm with CN B/L (10 L/M Rolls)	28.1 kgs
DL121500L	12mm x 1500mm with CN B/L (10 L/M Rolls)	28.1 kgs
DL122000L	12mm x 2000mm with CN B/L (10 L/M Rolls)	37.4 kgs
DL202000L	20mm x 2000mm with CN B/L (10 L/M Rolls)	43.4 kgs