

# Regline 60 Lining Rubber

Regline 60 Lining Rubber is a premium grade wear and impact resistant 60 Duro rubber lining with a CN bonding layer.

## FEATURES

Regline 60 Lining Rubber is made from a highly elastic premium rubber compound and will display excellent resistance to sliding abrasion and large particle impact.

Regline 60 has excellent physical properties including cut and tear resistance. It will also display resistance to some mild chemicals, including acids and alkalis used in mineral processing. It has good ozone/UV resistance making it suitable for outdoor use.

Regline 60 features a specially formulated Neoprene based CN bonding layer to achieve ultimate adhesion when bonded to steel or rubber surfaces. The CN bonding layer is compatible with a wide range of Neoprene based rubber adhesives and allows for good bond strength to be achieved even in adverse conditions encountered on site.



## TECHNICAL INFORMATION

Polymer	NR/BR	
Colour	Black with CN bonding layer	
Specific Gravity	1.10	ASTM D297
Hardness	60° ± 5° Shore A	ASTM D2240
Tensile Strength	17 MPa (min)	ASTM D412
Elongation @ Break	450% (min)	ASTM D412
Abrasion	60mm <sup>3</sup> (max) @ 10N	ASTM D5963
Temperature Range	-20°C to + 70°C	
Tear Strength	80 N/mm (min)	ASTM D624

### AVAILABLE SIZES

Reglin stock Regline 60 Lining Rubber in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

PART NO.	DESCRIPTION	WEIGHT (PER L/M)
REG6003	3mm x 1500mm ( 10 L/M Rolls)	6.2 kgs
REG6006	6mm x 1500mm ( 10 L/M Rolls)	10.7 kgs
REG6010	10mm x 1500mm ( 10 L/M Rolls)	16.5 kgs
REG60102000	10mm x 2000mm ( 10 L/M Rolls)	22 kgs
REG6012	12mm x 1500mm ( 10 L/M Rolls)	20.7 kgs
REG60122000	12mm x 2000mm ( 10 L/M Rolls)	27.6 kgs
REG6016	16mm x 1500mm ( 10 L/M Rolls)	26.4 kgs
REG6020	20mm x 1500mm ( 10 L/M Rolls)	33 kgs
REG60202000	20mm x 2000mm ( 10 L/M Rolls)	44 kgs
REG6025	25mm x 1500mm ( 10 L/M Rolls)	43.2 kgs
REG60501800	50mm x 1800mm ( 10 L/M Rolls)	103.7 kgs