

# Reg-Lag 60 Sheet Lagging

Reg-Lag 60 Sheet Lagging is a premium grade wear resistant 60 Duro rubber pulley lagging sheet with CN bonding layer.

## FEATURES

Reg-Lag 60 Sheet Lagging is made from a highly elastic premium natural rubber compound and will display excellent resistance to abrasion.

Featuring a diamond profile surface, this sheet lagging improves the coefficient of friction between the pulley and conveyor belt, reducing slippage and preventing material buildup by shedding dirt and water away from the pulley.

It also features a CN bonding layer to achieve ultimate adhesion when bonded to pulley surfaces and allows for good bond strength to be achieved even in adverse conditions encountered on site.

Reg-Lag 60 Sheet Lagging is supplied in roll form for easy application to the pulley in a single sheet and is compatible with a wide range of cold bonding rubber adhesives.



## TECHNICAL INFORMATION

Polymer	NR/BR	
Colour	Black with CN bonding layer	
Specific Gravity	1.10	
Hardness	60° ± 5° Shore A	ASTM D2240
Tensile Strength	20 MPa (min)	ASTM D412
Elongation @ Break	450% (min)	ASTM D412
Abrasion	90 mm <sup>3</sup> (max) @ 10N	ASTM D5963
Temperature Range	-20°C to +70°C	
Tear Strength	80 N/mm (min)	ASTM D624

## AVAILABLE SIZES

Reglin stock Reg-Lag 60 Sheet Lagging in a range of standard thicknesses and roll sizes.

PART NO.	SIZE	WEIGHT (PER L/M)
DL081500M	8mm x 1500mm (Mini) with CN B/L (10 L/M Rolls)	18.6 kgs
DL081500	8mm x 1500mm (Standard) with CN B/L (10 L/M Rolls)	18.6 kgs
DL101500	10mm x 1500mm (Standard) with CN B/L (10 L/M Rolls)	23.1 kgs
DL121500	12mm x 1500mm (Standard) with CN B/L (10 L/M Rolls)	28.1 kgs
DL121500L	12mm x 1500mm (Large) with CN B/L (10 L/M Rolls)	28.1 kgs
DL122000L	12mm x 2000mm (Large) with CN B/L (10 L/M Rolls)	37.4 kgs
DL202000L	20mm x 2000mm (Large) with CN B/L (10 L/M Rolls)	43.4 kgs

## DIAMOND PROFILES

