Sheet Rubber



Neoprene HG Rubber Sheet

Reglin Neoprene HG is a premium grade, weather, heat and flame resistant rubber sheet.

FEATURES

Reglin Neoprene HG Rubber Sheet is made from a premium Neoprene rubber compound and will display high temperature and flame resistance.

Neoprene HG has excellent physical properties including mechanical strength and abrasion resistance and has the capability for high load bearing. It has excellent ozone/ UV resistance making it weather resistant and suitable for prolonged outdoor use.

Neoprene HG exhibits good resistance to oil and petroleum based products including a range of fuels, greases, solvents and hydraulic fluids. It will also display moderate chemical resistance to acids and alkalis.

Neoprene HG is F.R.A.S. (Fire-resistant and Anti-static) rated. It is independently tested and certified by the Mine Safety Technology Centre to meet MDG 3006 / MDG 3608 Non-metallic Materials for use in Underground Coal Mines.



TECHNICAL INFORMATION

| Polymer | CR | |
|--|--|-------------|
| Polymer Content | 80% | |
| Colour | Black | |
| Specific Gravity | 1.4 | ASTM D297 |
| Hardness | 75° ± 5° Shore A | ASTM D2240 |
| Tensile Strength | 14 MPa (min) | ASTM D624 |
| Elongation @ Break | 300% (min) | ASTM D412 |
| Abrasion | 170mm ³ (max) @10N | ASTM D5963 |
| Temperature Range | -25°C to +110°C | |
| Compression Set 22 hrs @ 70°C | 25% (max) | ASTM D395 B |
| Heat Age Properties 70 hrs @ 100°C Hardness Change Tensile Change Elongation Change | 0/+15° Shore A (max) +/-15% (max) -40% (max) | ASTM D573 |
| Ozone Resistance 100 hrs @ 100pphm, 20% Strain, 40°C | No Cracks | ATM D1149 |



www.reglinrubber.com.au



AVAILABLE SIZES

Reglin stock Neoprene HG Rubber Sheet in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes and gaskets to suit your application requirements.

| PART NO. | SIZE | WEIGHT (PER L/M) |
|-----------|-------------------------------|------------------|
| NEOBP01.5 | 1.5mm x 1200mm (10 L/M Rolls) | 2.7 kgs |
| NEOBP03 | 3mm x 1200mm (10 L/M Rolls) | 5.2 kgs |
| NEOBP04.5 | 4.5mm x 1200mm (10 L/M Rolls) | 7.8 kgs |
| NEOBP06 | 6mm x 1200mm (10 L/M Rolls) | 10.3 kgs |
| NEOBP10 | 10mm x 1200mm (10 L/M Rolls) | 17.2 kgs |

STANDARDS

Reglin Neoprene HG Rubber sheet conforms with MDG 3608 Certification can be supplied upon request.

